




ASRA[™] 6636

Always check the website for the most updated specifications: www.americh.com










All bathtub dimensions are ± 1/2".

Airbath System II

Blower must be remotely located

(Diagram is required for custom blower connection locations)



LEGEND:

) BLOWER OUTLET

REMOTE CONTROL (INVISIBLE MAGNETIC HOLDER)

STANDARD EQUIPMENT:

- Americh Remote Control
- Integral Waste & Overflow with Polished Chrome trim Available with polished brass, polished nickel, satin nickel or oil rubbed bronze trim at no additional charge if specified at the time of order. Requests after order is shipped are subject to a \$75 list charge for trim

INSTALLATION TIPS

- Install product according to Owners Manual and local codes.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.

DIMENSIONS

66" x 36" x 22" (1676 x 914 x 559 mm) Gallon to Overflow = 90 (Liters = 341)

MATERIAL: Acrylic (All Americh Standard Colors) Dual Color Available (Premium Color Upcharge)

TUB FLOOR: NON-Textured

UNDERMOUNT: No

OPTIONAL ACCESSORIES

- Pillows: 13"
- Linear Overflow

CODES AND COMPLIANCE

Americh products meet or exceed these standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1

Contact Americh for additional approvals.