

US-2215 Swanstone Undermount Single Bowl Kitchen SInk

Manufactured from Swanstone solid surface

WARRANTY Limited Lifetime - Residential Limited 10-year - Commercial


(See page 2 for detailed information.)

Recommended for high-use traffic areas and commercial surfaces.

FEATURES

8³/4

- Reinforced solid surface means color and texture run all the way through and cannot wear away.
- · Mounts underneath your choice of countertop for high-design appeal.
- · Heat, stain, and scratch resistant for lasting beauty.



Capacity: 9-3/4 gallons

- 35/8'

SPECIFICATIONS

US-2215 Swanstone Undermount Single Bowl Kitchen Sink

| Model | Part | Nominal Dimensions | Ship Wt. Lb. | Ship FedEx | Carton Dims. In. | Cu. Ft. |
|---------|-----------|--|-----------------|---------------|---------------------|---------|
| US-2215 | US02215SB | 25" W x 21-1/4" D (635 mm x 540 mm) | 25 | FedEx | 28 x 24 x 12 | 4.67 |

COLORS

Solid Colors:

- White (010)
- Bisque (018)
- Bone (037)

Aggregate Colors:

- Arctic Granite (035)
- Baby's Breath (168)
- Barley (091)
- Bermuda Sand (040)
- Black Galaxy (015)
- Canyon (124) Я • Glacier (121) Я
- Gray Granite (042)

KITCHEN SINKS

Our Planet Colors

• Night Sky (012)

• Pebble (072)

• Prairie (122) Я

• Tahiti Desert (050) • Tahiti Gray (053)

• Tahiti Ivory (059)

• Tahiti Matrix (058)

• Tahiti Sand (051) • Tahiti White (011)

STANDARDS AND RATINGS

American National Standard Institute-ANSI Z124.6 International Association of Plumbing and Mechanical Officials (IAPMO)-Listed cUPC listed-Certified to CSA Test Standard B45.5 by IAPMO Uniform Plumbing Code (UPC) National Sanitation Foundation-NSF/ANSI 51 Food Equipment Materials

For a complete list of tests and results see the Technical Data Sheet.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

MAINTENANCE AND CLEANING INFORMATION

Clean your Swanstone sink by using abrasive cleaners or other similar products. Use of a nylon scouring pad or Mr. Clean[®] Magic Eraser[®] is also recommended. Food-based stains can be removed using a 50-50 mix of bleach and water solution and soaking for 15 minutes. For rust or other mineral stains. rust-removing products are acceptable. **Do not** use metal scouring pads.