

Lavatory Faucet SLS-5510-1.5, SLS-5512-1.5 **Specification Submittal**



Model Numbers

- □ SLS-5512-1.5 Lavatory Faucet with pop-up drain assembly
- ☐ SLS-5510-1.5 Lavatory Faucet only

Options / Modifications

Append appropriate -suffix to model number

- □ 66 -0.5-NA 0.5 gpm (1.9 L/min) non-aerated laminar flow outlet
- □ cc -1.0 1.0 gpm (3.8 L/min) flow rate restrictor
- □ -DP4 4 inch deck plate

Feature Highlights

- Single post round lavatory faucet with swival lever handle
- Single hole deck mounting and optional 4 inch deck plate
- Commercial grade 1/4 turn ceramic disc valve cartridge for drip free performance
- Pop-up drain and lift rod assembly (SLS-5512 only)
- 3/8 inch copper supply lines with 1/2 inch IPS fittings
- Aerator with standard 1.5 gpm flow rate (5.7 L/min) Optional aerator available in lower flow rates
- Metal construction
- Polished chrome finish (standard)

Standards / Certifications

- ASME A112.18.1/CSA B125.1
- NSF/ANSI 61.9, NSF/ANSI 372
- WaterSense 1.0 and 1.5 gpm only

Cartified by



Finish Options / Modifications

Append appropriate -suffix to model number

- ☐ -STN Satin Nickel
- □ -SBZ Seasoned Bronze

Warranty

- Limited Lifetime to the original end purchaser in consumer installations
- 5 years for commercial installations



